



The CML Entry Level Series is tailored to meet from low to high volume production requirements. With the Entry Level Series, you get the features you need, without paying for extras you don't. The E350R series features a heavy-duty 1 or 2 moving blade solution with higher horsepower ratings for higher volume customers. The E350R is a heavy-duty machines with even more horsepower that provides a wider cutting area with 3 or 4 moving blade possibilities in high volume environments. Whatever your requirements, Cml offers an edger to meet your needs.

#### CML

Cml has industry-leading edgers to help you successfully optimize the use of all material. Designed to meet your unique production requirements, the high performance CML edger optimize materials and minimize costs. CML edgers deliver high quality cuts with limitless application possibilities. Whatever your requirements. CML has a edger to help you make the most of every situation.


#### Cml Features

- Heavy-duty Dip chain feed belt with hardened steel guides
- 4 top pressure roller with Extended pressure board
- Precision surface treated Arbour shaft and moving heads
- Operator adjustable 15mw lasers
- Complete range of optimization solutions

**CML ENGINEERING S.R.L.**  
Advanced Equipment  
Intelligent Integration  
Experienced Consulting  
Incomparable Services  
E-mail [info@cml-engineering.it](mailto:info@cml-engineering.it)



Technical Specifications	CML Edger E350 R
Voltage	400V / 50Hz
Dust Connection (MAIN)	250mm diametro - 30 m/s (portata) - 5300Mc3/h
Machine Weight	2000
Machine Dimensions	Lunghezza 173cm
	Larghezza 175cm
	Altezza 175cm
Main Drive Motor	Hp 30 / Kw 22
Feed Belt Motor	1.5Kw
Feed Belt Speed	0 a 36 Mt/1"
Maximum pass thru width	650mm
Feed belt width	350mm
Maximum Balde speed	3500 RPM
Maximum board Thickness	105mm (370mm Blade)
Minimum board Thickness	20mm
Minimum board Length	600mm (350mm with optional – small pieces)
Minimum board Width between fixed and moving blade	16mm
Maximum distance between fixed and moving table	300mm (both moving heads installed)
Maximum distance between fixed and moving table	320mm (only one moving heads installed)
Maximum distance between two and moving table	300mm (no fixed blade)
Table working height from floor	780mm
Control panel for cutlist with up to 99 different program ( Manual or automatic control)	
Position laser control (beam color red. Power 15mw maximum range 6m)	



Sede legale : Via Torri Bianche 1 - 20871 VIMERCATE (MI) – ITALY  
 Sede operativa : Via G. Galilei, 34/36 – 20060 GESSATE (MI) - ITALY  
 Tel 0039-02-95384207  
 Fax 0039-02-95384223

**E-mail : [info@cml-engineering.it](mailto:info@cml-engineering.it) – Web : [www.cml-engineering.it](http://www.cml-engineering.it)**